5037786635

TO: 915712738300

P.001/002



RECEIVED CENTRAL FAX CENTER

APR 2 8 2006

Problem solved.



To:	Examiner Alicia Толгез	From: Steven Schad
	Group Art Unit 3671	Pages: 2
Fax	571-273-8300	Date: 4/28/2006
Re:	Serial No. 10/714,884	cc:

Dear Ms. Torres,

Thank you for your telephone call today. As mentioned in my telephone message, I propose to amend the claim to remove the alternative language. With the alternative language removed, the objection to the drawings should be overcome.

We will also need to cancel claim 131.

Stoon Schol

If you are accepting of the attached amendment of claim 129 and the canceling of claim 131, I hereby approve the changes by examiner's amendment.

If you accept this proposal by May 1, 2006, no extension fee is required. If, however, an extension or other fee is required, then, I authorize charging the fee to Deposit Account No. 50-3585.

Thanks.

Steven Schad Reg. No. 32,550

> World Headquarters 2141 NW 25th Avenue Portland, Oregon 97210-2578

Phone: 503,228,2141 Fax: 503,499,6082 www.escocorp.com

BEST AVAILABLE COPY

5037786635

APR-28-2006~17:26 FROM:ESCO ADMIN 2

TO: 915712738300

P.002/002

129. (Currently Amended) A wear assembly for an excavator having a digging edge, the wear assembly comprising an adapter fixed to the excavator, a wear member, and a lock to secure the wear member to the adapter, one of the adapter and wear-member having a nose and the other of the adapter and wear member having a socket for receiving the nose, the nose and the socket wear member each having converging walls converging toward a front end, and opposite sidewalls, one of the socket or nose including at least one rail extending from a sidewall thereof and oriented at the same general inclination as one of the converging walls, and the other of said socket or nose including at least one groove into which the rail is received, wherein the socket is defined by opposed converging surfaces each extending at an inclination to the longitudinal axis of the socket and by side surfaces wherein at least one said side surface includes a lateral surface between the converging surfaces as a part of the at least one groove to engage the rail, and wherein each said lateral surface faces toward one of the converging surfaces and extends generally in the same inclined direction relative to the longitudinal axis as the converging surface the lateral surface faces.